

## AMILO Display SL 3220W 22 Inch LCD widescreen Display

Issue August 2008

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. The AMILO Display SL 3220W widescreen display offers best performance for the home office and multimedia, such as photo editing, gaming and watching the latest DVD. With its extremely slim and stylish design, the AMILO Display SL 3220W fits perfectly into your home environment.

### Highlights

- 22-inch widescreen display for a high definition video support up to 1080i with HDCP content protection
- Stylish black design with a piano black glossy front
- Frame rate conversion
- Theme mode for optimized picture
- DVI-D input supports HDCP

### Ergonomics

- Optimum flicker-free and distortion-free picture
- Excellent color purity
- Well balanced brightness uniformity
- Excellent Advanced Contrast Ratio (5,000:1)
- Space saving design

### Technical highlights

- 22" (55.9 cm) LCD widescreen display
- Excellent contrast (ACR) 5,000:1
- Brightness 300 cd/m<sup>2</sup>
- Fast response time (typ.) 5 ms
- Internal power supply

### Reliability

- Display Lifetime Extender
- Low power consumption
- Power management according to EPA
- Guaranteed quality and stability



RESPONSE TIME



ACR CONTRAST



HDCP



SPEAKER

<b>Visible screen diagonal</b>	22 inch (55.9 cm)
<b>Resolutions</b>	
Pixels	1680 x 1050
Pixels*	1280 x 768
* expanded	
<b>Picture size</b>	473.76 x 296.1 mm
<b>Colors</b>	16.7 million
<b>Pixel Pitch</b>	0.282 mm
<b>Frequencies</b>	
Horizontal	31 - 83 kHz
Vertical	56 - 76 Hz
<b>Brightness (typical)</b>	300 cd/m <sup>2</sup>
<b>Advanced Contrast Ratio</b>	5,000:1
<b>Viewing angle at CR &gt; 5:1</b>	
Horizontal	170°
Vertical	170°
<b>Response time (typical)</b>	5 ms
<b>Plug and Play</b>	VESA DDC/ CI
<b>Setting options</b>	
Menu language (16 languages)	
Power saving mode with Lifetime Extender	
Input signal select	
Theme Mode	
Brightness (Back light control)	
Contrast, Volume control	
Picture position (horizontal and vertical), H-size, Phase,	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Factory recall setting	
<b>OSD Language</b>	
English, German, French, Italian, Spanish, Portuguese,	
Swedish, Dutch, Finnish, Danish, Norwegian,	
Russian, Polish, Hungarian, Czech and Turkish	
<b>Base</b>	
Tilt angle	-5° / +15°
<b>Video input</b>	1x D-SUB, 1x DVI-D (HDCP support)
<b>Audio input / output</b>	
Audio signal input	3.5 mm stereo phone jack
Audio output	1.5 W (L) + 1.5 W (R)

<b>Electrical values</b> (internal power supply)	
Rated voltage	100 - 230 V
Frequency	50 - 60 Hz
Power draw (EPA)	
EPA 'On Mode'	27 W
Max.	< 41 W
Stand by	< 0.8 W
Protection class	1
<b>Temperatures/ dimensions/ weight</b>	
Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D):	
(with stand)	424x 510 x 226 mm
Weight (Monitor only)	4.94 kg
<b>Reliability</b>	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight	30,000 h
(brightness > 50 % of original brightness)	
<b>Compliance with standards</b>	
Product safety	EN60950
Ergonomics	ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 2004/108/EEC (EN55022/B, EN55024 EN61000-3-2/-3)
<b>Ecology</b>	RoHS, IT-Eco-declaration, Energy Star (EPA 4.1)
<b>Accessories</b>	
Power cable (1.8 m)*	1x wall socket (Euro-Schuko-Type CEE7)
Data cable (1.8 m)*	D-SUB (15-pin)
Audio cable (1.8 m)*	3.5 mm stereo phone jack
* detachable on display	
<b>Special features</b>	Standardized mounting interface according VESA FPMPI (100 mm) Kensington Lock
<b>Order code</b>	S26361-K1289-V181
<b>EAN</b>	4333643810641
<b>SAP order name</b>	AMILO LSL 3220W