

Fujitsu recommends Windows 8 Pro.

Data Sheet

Fujitsu ESPRIMO E710 E90+ Desktop PC

Your Desktop PC Without Any Compromises

Fujitsu ESPRIMO E710 PCs bring you highly expandable technology for your challenging business applications. The use of identical components within the product family ensures perfect infrastructure compatibility and simplifies rollout. A 92%-efficient power supply will ensure environmental compliance for years to come. Intel® Standard Manageability Technology keeps administration costs to a minimum. Plus, EraseDisk ensures secure system retirement



Small form factor PC

Flexible desktop solution whatever the space required

- Less than 13 liters volume, can be positioned vertically and horizontally

Energy efficiency

Low power consumption and low costs, without any loss in performance

- Sophisticated technology, switched monitor outlet, low energy-consuming processors and enhanced power management settings



Green technology

Fujitsu's contribution to environmental protection for the continued existence of our planet

- Halogen-free printed circuit of mainboard and power supply, sophisticated product concept for the entire lifecycle

Quiet

Pleasant working environment due to an extremely quiet system

- Innovative hardware design, optimized cooling concept ensures silent operations

Serviceability

Easy to extend and optimal user-friendliness without any additional tools

- Easy access to all replaceable and expandable components



Components

Processor	<p>Intel® Core™ i7-3770 processor (4 Cores / 8 Threads, 3.40 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics 4000) *</p> <p>Intel® Core™ i5-3570 processor (4 Cores / 4 Threads, 3.40 GHz, up to 3.8 GHz, 6 MB, Intel® HD Graphics 2500) *</p> <p>Intel® Core™ i5-3470 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 2500) *</p> <p>Intel® Core™ i3-3220 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2500)</p> <p>Intel® Core™ i3-2130 processor (2 Cores / 4 Threads, 3.40 GHz, 3 MB, Intel® HD Graphics 2000)</p> <p>Intel® Core™ i3-2120 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2000)</p> <p>Intel® Pentium® processor G870 (2 Cores / 2 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics)</p> <p>Intel® Pentium® processor G860 (2 Cores / 2 Threads, 3.00 GHz, 3 MB, Intel® HD Graphics)</p> <p>Intel® Pentium® processor G850 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel® HD Graphics)</p> <p>Intel® Pentium® processor G645 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel® HD Graphics)</p> <p>Intel® Pentium® processor G640 (2 Cores / 2 Threads, 2.80 GHz, 3 MB, Intel® HD Graphics)</p> <p>Intel® Celeron® processor G550 (2 Cores / 2 Threads, 2.60 GHz, 2 MB, Intel® HD Graphics)</p> <p>Intel® Celeron® processor G540 (2 Cores / 2 Threads, 2.50 GHz, 2 MB, Intel® HD Graphics)</p> <p>*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)</p>
Operating systems	
Operating system	<p>Windows 8 Pro</p> <p>Windows 8</p> <p>Windows® 7 Professional 64-bit</p> <p>Windows® 7 Professional 32-bit</p> <p>Windows® 7 Home Premium 64-bit</p> <p>Windows® 7 Home Basic (EM) 32-bit</p>
Operating system compatible	<p>openSUSE Linux</p> <p>Windows® XP</p>
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	<p>2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM</p> <p>4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM</p> <p>8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM</p>
Hard disk drives (internal)	<p>SSD SATA III, 256 GB, 2.5-inch</p> <p>SSD SATA III, 128 GB, 2.5-inch, SED</p> <p>SSD SATA III, 128 GB, 2.5-inch</p> <p>SSD SATA II, 128 GB, 2.5-inch, FDE</p> <p>HDD SATA III, 7200 rpm, 2000 GB, 3.5-inch</p> <p>HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch</p> <p>HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical</p> <p>HDD SATA III, 7200 rpm, 500 GB, 3.5-inch</p> <p>HDD SATA III, 7200 rpm, 250 GB, 3.5-inch</p> <p>HDD SATA II, 7200 rpm, 320 GB, 2.5-inch</p> <p>HDD SATA II, 7200 rpm, 160 GB, 2.5-inch</p>
Hard disk notes	Up to 18 GB of HDD space is reserved for system recovery
Graphics add on cards (optional)	<p>NVIDIA® Quadro® NVS 300 LP, 512 MB</p> <p>NVIDIA® GeForce® GT630 DisplayPort 2GB LP 0-Watt, 2 GB</p> <p>NVIDIA® GeForce® 605 DisplayPort 1GB LP, 1 GB</p> <p>LFH59/ 2x DVI-I adapter cable</p> <p>DP to DVI-D (single link) Adapter Cable</p> <p>2nd NVIDIA® Quadro® NVS 300 LP, 512 MB</p>

Drives (optional)	BD Triple Writer SATA slim (tray) DVD-ROM DVD Super Multi MultiCard Reader 24in1 USB 2.0 3.5"
Interface add on cards/components (optional)	WLAN III, 802.11g/Draft-n (Windows only, dedicated regions only) Parallel Interface Gigabit Ethernet PCIe x1, DS eSATA Interface Dual serial card PCIe x1, powered Dual serial card PCIe x1
Base unit	ESPRIMO E710 E90+
Mainboard	
Mainboard type	D3161
Formfactor	µATX
Chipset	Intel® Q75
Processor socket	LGA 1155
Processor quantity maximum	1
Memory slots	4 DIMM (DDR3)
Supported capacity RAM (max.)	32 GB
Memory frequency	1600 MHz
Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same.
LAN	10/100/1000 MBit/s Intel® 82579 V
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Conexant CX20642
Audio features	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	5
thereof SATA III	1
thereof eSATA	2 (optional)
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	10
USB 3.0 total	4
USB front	4x 2.0 or 2x 2.0/ 2x 3.0
USB rear	6x 2.0 / 2x 3.0
USB internal	2
VGA	1 (via DVI to VGA adapter, part of shipment)

Interfaces

DisplayPort	1
DVI	1 (DVI-I)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

Input device / components

	Optical USB wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse KBPC PX ECO Mouse M440 ECO

Drive bays

Drive bays total	3
3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	optional external bay as internal 3,5"

Slots

PCI-Express 3.0 x16	1 x (200 mm / 7.87 inch) Low profile
PCI-Express 2.0 x4 (mech. x16)	1 x (200 mm / 7.87 inch) Low profile
PCI-Express x1	1 x (174 mm / 6.85 inch) Low profile
PCI (32-bit / 33 MHz)	1 x (174 mm / 6.85 inch) Low profile
Slots optional configuration	or 2x PCI full high via Riser

Graphics on board

Graphics brand name	Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU)
Shared video memory	up to 1759 MB
TFT resolution (VGA)	1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DisplayPort)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel 2560 x 1440 pixel 2560 x 1600 pixel

Graphics on board

Graphics features	Dual display support DirectX® 10.1 or DirectX® 11 (depending on CPU) HDCP support Open GL® 3.3 (depending on CPU) Open CL™ 1.1 (depending on CPU) For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows 7® only)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 88% / 92% / 91%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	Switched

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=6fd6a36c-d028-4e30-9bc0-4096bb402d31

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
-------------------------------	------------------------------------

Noise emission

Related Processors for noise	Core i5-3770
Standard noise emission	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	3.6 B / 22 dB(A) Bystander; 26 dB(A) Operator position
Standard noise operation mode: HDD load	3.5 B / 21 dB(A) Bystander; 24 dB(A) Operator position
Standard noise operation mode: Idle mode	3.2 B / 19 dB(A) Bystander; 22 dB(A) Operator position
Standard noise operation mode: ODD load	4.7 B / 33 dB(A) Bystander; 40 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	3.2 B / 19 dB(A) Bystander; 22 dB(A) Operator position
Blue angel noise emission according certification	According to ISO 7779:2010, ECMA-74 for max. possible configuration
Blue angel noise notes / description	A weighted sound power level Lwad (in B); 1B = 10dB
Blue angel noise operation mode: HDD load	3.7 B = 37 dB
Blue angel noise operation mode: Idle mode	3.7 B = 37 dB
Blue angel noise operation mode: ODD load	4.7 B = 47 dB

Dimensions / Weight / Environmental

Dimensions (W x D x H)	340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch
Operating position	horizontal / vertical (optional, feet needed)
Weight	10 kg

Dimensions / Weight / Environmental

Weight (lbs)	22.05 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35°C (50 - 95°F)

Compliance

Product	ESPRIMO E710
Model	DT8
Germany	TÜV GS
Europe	CE Nordic Swan in progress
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 5.0 (dedicated regions) EPEAT® Gold (dedicated regions)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/

Additional Software

Additional software (preinstalled)	Nero Essentials S (burning software) Fujitsu Recovery (Hard Disk Based Recovery) Norton Internet Security (incl. Firewall) 60 days version Don't forget Office.
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics) Nero 10 Essentials XL

Miscellaneous

Keyboard on (Special Fujitsu keyboard required)
Thermal management
Extended lifetime

Compatibility (references)

DMI 2.0
PC 2001
WMI 1.5
USB 2.0
SMBIOS

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) Intel® Standard Manageability WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Manageability link	http://ts.fujitsu.com/manageability

Security	
System protection	Kensington Lock support Eye for padlock Optional: Integrated cabinet lock
Audit proof protection	EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 1.2) Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
Access protection	User and supervisor BIOS password Hard disk password Optional: Access protection via external SmartCard reader Optional: Access protection via internal SmartCard reader

Serviceability	
	EasyFix EasyChange for HDD EasyChange for optical drives

Packaging information	
Packaging dimension (mm)	467 x 265 x 540 mm
Packaging dimension (inch)	18.39 x 10.43 x 21.26 inch
Max. quantity / pallet	28
Material - Weight (g) Carton	1140 g
Material - Weight (lbs) Carton	2.51 lbs
Material - Weight (g) EPS / PS	180 g
Material - Weight (lbs) EPS / PS	0.4 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process

Warranty	
Standard Warranty	1 year
Service level	Bring-In / On-Site Service (depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://www.fujitsu.com/fts/services/support/index.html

Recommended Accessories

Wireless Keyboard Set LX900



The Wireless Keyboard LX900 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.

S26381-K564-L4** (**: Country specific variation)

SOUNDSYSTEM DS E2000 Air



The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

Order Code:
S26391-F7128-L600

WebCam 130 HD2



With the most advanced HD (High Definition / 720p) recording feature and widescreen video format (16:9 and 16:10), WebCam 130 HD2 can capture up to 30 frame rate per second, close up to HD/720p quality video. Even more: 1-Click-Upload makes the video uploading to YouTube in a snap! With smart clip for notebook & LCD display it is easy to install on any device you want.

Order Code:
S26391-F7136-L5

HS E2000 Communicator Headset



The Fujitsu HS E2000 Communicator headset allows you to use your personal computer for Voice over IP (VoIP) in stereo audio quality. This premium headset is designed to provide superb audio quality and comfort for the telephony, internet chat, speech recognition, video conferencing and multimedia applications.

Order Code:
S26391-F7139-L5

CELVIN® Drive D100



The CELVIN® Drive D100 is a highly reliable external storage device with a standard USB-interface for easy Plug & Play use with a notebook or PC. It is also easy to set up additional home network capacity by connecting it with dedicated routers or NAS devices.

Order Code:
S26341-F103-L118

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu ESPRIMO E710 E90+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO E710 E90+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions
Website: www.fujitsu.com/fts
2012-11-16 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions